

Data sheet for Camper Trolley

	CT1500	CT2500	CT2500RS	CT4500
Signal Frequency	2.4GHz	2.4GHz	2.4GHz	2.4 GHz
Signal Power	-20~4.5dbm	-20~4.5dbm	-20~4.5dbm	-20~4.5dbm
Rated Voltage	14.8V	14.8V	24V	24V
Rated Current	20A	40 A	30A	30A
Starting Peak Current	Max. 150A	Max. 150A	Max. 150A	Max. 150A
Battery operating capacity	Approx. 30 min. operation	Approx. 30 min. operation	Approx. 30 min. operation	Approx. 30 min. operation
Battery capacity	6.6AH	11AH	11AH	11AH
Battery charger	100-240 VAC, 16.8VDC/2A	100-240 VAC, 16.8VDC/2A	100-240 VAC, 29.4VDC/2A	100-240 VAC, 29.4VDC/2A
Remote control battery	2xAA 1.5Volt	2xAA 1.5Volt	2 x AA 1.5Volt	2 x AA 1.5Volt
Max. load stress	300 kg	300 kg	300kg	450 kg
Speed unloaded	Approx. 9 m/min	Approx. 9 m/min	Approx. 15.5 m/min.	Approx. 9 m/min
Speed loaded	Approx. 7 m/min	Approx. 7 m/min	Approx. 12.5 m/min.	Approx. 7 m/min
Climbing Incline Limitation	Max. 10%	Max. 10%	Max. 10%	Max. 8%
Safety function	3 min. Auto shut-off	3 min. Auto shut-off	3 min. Auto shut-off	3 min. Auto shut-off
Hauling capacity	Trailers up to 1,500 kg	Trailers up to 2,500 kg	Trailer up to 2,500 kg	Trailer up to 4,500 kg
Tracks	2 with rubber profiles	2 with rubber profiles	2 with rubber profiles	2 with rubber profiles
Weight	Approx. 20 kg	Approx. 35 kg	Approx. 35 kg	Approx. 35 kg
Tower height	Low (foldable)	High (EU) / Low (AUS/USA)	Low	Low
Chassis bracket	C-channel	C-channel (EU) / Closed frame (AUS/USA)	C-channel (EU) / Closed frame (AUS/USA)	None